

Name DuPont™ Residential Sealant



Product ID MSDS 130000106198 Classification 07 92 13.00 Thermal and Moisture Protection (insulation water barrier): Elastomeric Joint Sealants

Website www.dupont.com/products-and-services/construction-materials/building-envelope-systems/brands/water-barrier-systems/products/dupont-residential-sealant.html

Manufacturer E.I. du Pont de Nemours and Company Contact Name Nicole Murphy Title Product Manager

Address 1007 Market Street Wilmington, DE 19898 Phone Phone Email 1-800-448-9835

Description DuPont™ Residential Sealant is a durable, highly flexible window sealant for use in general residential construction. It is formulated to bond well with DuPont™ Tyvek® weather barriers, and other DuPont construction products, as well as most common building materials. As an integral part of a complete building envelope system, DuPont™ Residential Sealant helps control both air and water intrusion, to help make homes more comfortable, prevent water damage, and reduce heating and cooling costs. Exposure to any hazards associated with the inputs mentioned are not present in the finished form of DuPont™ Residential Sealant. The ingredients listed which trigger the hazards mentioned are inert within the finished form of DuPont™ Residential Sealant. This product is manufactured by Tower Sealants for DuPont™. For additional product information call: 1-800-424-9300.

Release Date 2014-10-07 Expiry Date 2017-10-07 HPD URL https://tool.hpdcollaborative.org/uploads/files/hpds/270/1490-20141007153413.pdf

Self-declared Second Party Third Party

Certifier Certificate #

SUMMARY DISCLOSURE

The content of this product was assessed for health hazard warnings as required using Pharos

Residuals Disclosure Measured 100 ppm (ideal) Measured 1000 ppm Predicted by process chemistry As per MSDS (1,000 & 10,000 ppm) Not disclosed Other

Full Disclosure of Intentional Ingredients Yes No

Full Disclosure of Known Hazards Yes No

Disclosure Notes

Contents in Descending Order of Quantity

Undisclosed (Acrylic Polymer) , WATER , LIMESTONE; CALCIUM CARBONATE , Titanium dioxide , ETHYLENE GLYCOL , STODDARD SOLVENT , QUARTZ

Hazards PBT (Persistent Bioaccumulative Toxic) Cancer Gene Mutation

Development Reproductive Endocrine Respiratory

Highest concern GreenScreen score - Benchmark 1 Neurotoxicity Mammal Skin or Eye Aquatic toxicity Land toxicity Physical hazard Global warming Ozone depletion Multiple Unknown

Total VOC Content Material (g/L) 17.00 Regulatory (g/L) 26.00

Does the product contain exempt VOCs? N/A Yes No

Are there VOC-free tints available? N/A Yes No

Notes TiO2

Certifications + Compliance

VOC Emissions Not tested

VOC Content

Not tested

The HPD Standard is solely a declaration of product content and direct health hazards associated with exposure to its individual contents. It is not a full assessment of environmental impacts from the life cycle of this product. It is not an assessment of risks associated with actual use of the product. It does not address the potential health impacts of substances used or created during manufacture that do not appear in the final product as residuals, nor substances created during combustion or other degradation processes.

This Health Product Declaration was generated following the requirements of the noted Standard version and is valid for a total of three years after date of issue or three months after a substantive change of product contents occurs. Users should verify that this Health Product Declaration is compliant with the most current version of the HPD Standard. Accuracy of claims made in this Health Product Declaration is the sole responsibility of the listed manufacturer and certifier (if applicable). The HPD Collaborative does not warrant any claim made herein, explicit or implicit. The HPD Standard is an “open standard” developed and managed by the HPD Collaborative, a nonprofit organization. For more information, visit hpdcollaborative.org.

CONTENT IN DESCENDING ORDER OF QUANTITY

All ingredients must be assessed for health warnings against Priority Hazard Lists, regardless of disclosure level.

Priority Hazard Lists and information on the GreenScreen Benchmarks can be found at www.hpdcollaborative.org/hazardlists.

GS: GreenScreen Benchmark; **RC:** Recycled Content, **PC:** Post Consumer, **PI:** Post Industrial (Pre-consumer), **BO:** Both; **Nano:** comprised of nanoscale particles or nanotechnology

Name	CAS RN	% weight	GS	RC	Nano	Role
Hazard A	Warning A					
Hazard B	Warning B					
Hazard C	Warning C					
Hazard D	Warning D					
Hazard E	Warning E					
Notes						
Undisclosed (Acrylic Polymer)	Unknown	40 - 60 %		N	N	Body
Unknown	Not disclosed					
Proprietary components are withheld as a trade secret.						
WATER	7732-18-5	25 - 35 %	4	N	N	Flow agent
None found	No warnings found on HPD Priority lists					
LIMESTONE; CALCIUM CARBONATE	1317-65-3	5 - 15 %	LT-U	N	N	Filler
None found	No warnings found on HPD Priority lists					
Titanium dioxide	13463-67-7	1 - 10 %	LT-1	N	N	Colorant
CANCER	NIOSH-C: Occupational carcinogen (also in Prop 65, IARC, MAK)					
ETHYLENE GLYCOL	107-21-1	1 - 5 %	1	N	N	Plasticizer
DEVELOPMENTAL	NTP-OHAaT: A-Clear evidence of adverse developmental toxicant effects					
ENDOCRINE	TEDX: Potential Endocrine Disruptor					
MAMMALIAN	EU R-Phrases: R22: Harmful if swallowed.					

STODDARD SOLVENT	8052-41-3	0.75 - 1.25 %	LT-1	N	N	Thinning agent
CANCER	EU CMR (1): Carcinogen Category 2 - Substances which should be regarded as if they are carcinogenic to man (also in EU R-Phrases, EU H-Statements, EU CMR (2))					
GENE MUTATION	EU R-Phrases: R46: May cause heritable genetic damage. (also in EU H-Statements, EU CMR (2))					
MAMMALIAN	EU H-Statements: H304: May be fatal if swallowed and enters airways					
ORGAN TOXICANT	EU H-Statements: H372 Causes damage to organs through prolonged or repeated exposure					
MULTIPLE	VwVwS: Class 2 Hazard to Waters					

QUARTZ	14808-60-7	0.1 - 1 %	LT-1	N	N	Impurity
CANCER	IARC: Group 1: Agent is carcinogenic to humans - inhaled from occupational sources (also in NIOSH-C, MAK, NTP-RoC, Prop 65)					

CERTIFICATIONS AND COMPLIANCE

Certifying Party = First: Manufacturer's self-declaration; Second: Verification by trade association or other interested party; Third: Verification by independent certifier (ideal).

Applicable facilities = Manufacturing sites to which testing applies.

Type	Standard or Certification			Certifier or Laboratory
	Certifying Party	Issue Date	Expiry Date	Certificate URL
	Applicable Facilities			
	Notes			
VOC Emissions	N/A			
VOC Content	Not tested			
Recycled Content	Not tested			
Other				

ACCESSORY MATERIALS

This section is for additional products required by warranty or recommended by the manufacturer for installation (such as adhesives, fasteners, or factory coatings) or for maintenance, cleaning, or operations. Refer to Health Product Declarations, published separately, for a complete view of these products.

Note: This declaration is not intended to address hazards of the installation process.

Required or Recommended Product	URL for Companion Health Product Declaration
Condition when required or recommended and/or other notes	
DuPont™ Tyvek® Fluid Applied WB (VOC 25.00 g/L)	
DuPont™ Tyvek® Fluid Applied Weather Barrier Systems provide water and fluid applied air barrier protection designed for the unique demands of heavy commercial construction projects.	
DuPont™ Flashing Tape	
DuPont™ Flashing Tape helps protect the heads and jambs of rectangular doors and windows from air and water intrusion. Wind-driven rain and outdoor air can find their way into walls around windows and doors. By helping to seal the building envelope, self-adhered DuPont™ Flashing Tape can help reduce the risk of water damage, increase building comfort, and improve energy efficiency.	
DuPont™ Tyvek® Fluid Applied Flashing: Brush (VOC 25.00 g/L)	
A high quality, lower viscosity fluid applied flashing that can be brushed on for improved protection of complex window openings including effective application around recessed windows.	
DuPont™ Tyvek®; DuPont™ Tyvek® CommercialWrap®; DuPont™ Tyvek® CommercialWrap® D; DuPont™ Tyvek® StuccoWrap®; DuPont™ Tyvek® HomeWrap®; DuPont™ Tyvek® DrainWrap™	
There are many Tyvek® product types to meet your building protection, durability and aesthetic needs, including the products listed.	
DuPont™ Tyvek® Wrap Caps	
DuPont™ Tyvek® Wrap Caps are the recommended fastening method for DuPont™ Weatherization Systems. They provide additional protection around fastener penetrations and increases fastener-holding power.	
DuPont™ Tyvek® ThermaWrap™ R5.0	
DuPont™ Tyvek® ThermaWrap™ R5.0 offers the air and water management benefits of all DuPont™ Tyvek® weather barriers with an insulation R-value of 5.0. Compared to other exterior insulation products, the unique structure of Tyvek® ThermaWrap™ R5.0 allows any moisture that may get inside the wall to evaporate and the moisture vapor to escape to the outside, helping to prevent the accumulation of water in the wall and reducing the chance for water damage and mold.	
DuPont™ StraightFlash™ VF	
StraightFlash™ VF integrates easily with other DuPont weatherization products, including Tyvek® air and water barriers to help seal the building envelope. By protecting against water intrusion, StraightFlash™ VF helps prevent water damage to windows, doors. In addition, it can keep water out of wall systems and away from insulation helping to improve the insulation's durability and preserve its R-value.	
DuPont™ StraightFlash™	
DuPont™ StraightFlash™ door and window flashing provides premium protection against water intrusion. By sealing vulnerable areas around openings, StraightFlash™ can help improve the durability and energy efficiency of both homes and commercial structures.	
Tyvek® Tape: Seam Tape	
The best seam tape for sealing DuPont™ Tyvek® weather barriers against air and water in both residential and commercial construction. Finish the building envelope with a superior seam tape – DuPont™ Tyvek® Tape.	

DuPont™ Tyvek® Fluid Applied Flashing & Joint Compound (VOC 25.00 g/L)	
--	--

Fluid Applied Flashing & Joint Compound is an integral part of the DuPont™ Tyvek® Fluid Fluid Applied system, combining the functions of both flashing and joint compound into a single unique product to help increase job site efficiency by preventing lost time and material waste.

DuPont™ Sealant for Tyvek® Fluid Applied System (VOC 25.00 g/L)	
---	--

Is specifically designed for easy use with the DuPont™ Tyvek® Fluid Applied System: fills gaps around windows, doors and penetrations

NOTES